

Immersion Thermostat with MPC-Controller. Powerful pressure and suction pump made of industrial plastic material. Moistened parts in stainless steel or plastics. With adjustable overtemperature protection according to DIN 12876. Special Case: Acetone and Polyglycol: The plastic pump is not resistant against acetone and polyglycols (depending on the manufacturer). It is recommended that water is mixed with either glysantin or ethylene glycol for freeze protection. A more resistant plastic is available on request at an additional cost.

MPC-Controller:

Modern and easy to use microprocessor controller with a large temperature display.

Limited to essential functions only:

- * Large temperature display
 - * LED indicators for pump, cooling and heating
 - * Simple operation using only 3 keys
- Advanced:
- RS232/serial with the LAI commands G,v,L; (SpyLight compatible)
 - Pt100 sensor connection for sensor relocation (jacket control)

Technical data according to DIN 12876

Operating temperature range	25...200 °C
with water cooling	20...200 °C
with refrigerator	-30...200 °C
Temperature stability at 70°C	0,05 K
Temperature adjustment	digital
Temperature indication	digital
Internal temperature sensor	Pt100
Safety classification	Class III / FL
Heating power	1,5 kW
Pressure pump	
max. delivery	20 l/min
max. delivery pressure	0,2 bar
Suction pump	yes
max. delivery (suction)	17 l/min
max. delivery pressure (suction)	0,18 bar
Immersion depth	150 mm
Overall dimensions WxDxH **	132x153x312 mm
Net weight	3,4 kg
Power supply requirement	110V 1~ 50/60Hz
Power input	1,6 kW
max. current	15 A
Fuse	16 A
max. ambient temperature	40 °C
min. ambient temperature	5 °C



Order-No.: 2035.0004.99

from Serial-No.: 123655 1.0/10

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions. Illustrations can deviate from the original.

Accessories and periphery: , screw clamp #30541*, cooling coil #30554, dummy plugs, sleeve nuts thread M16x1, pump adaptor #19606, hose connector NW12 #6087, connection tubes, waterbaths in polycarbonat and stainless steel

* standard equipment

Output data valid for: Room temperature 20° C

Special Case: Acetone and Polyglycol: The plastic pump is not resistant against acetone and polyglycols (depending on the manufacturer). It is recommended that water is mixed with either glysantine or ethylene glycol for freeze protection. A more resistant plastic is available on request at an additional cost.

Standard delivery conditions - Power cable configuration:

1. Single-phase devices (230V/115V) -> with cable and plug
2. Three-phase devices with current consumption less than 63A -> with cable, without plug
3. Three-phase devices with current consumption greater than 63A -> without cable, without plug

** Please respect space requirements. See operating conditions at www.huber-online.com